

# Soil Vapour Implants & Accessories

## Surface Connections



1) Red Push on Plastic Cap.



2) Brass Sealing plug with Push-on fitting. No tools required. Dust cap included.



3) Swagelok cap to fit a Summa Cannister. In brass or stainless.



4) 1/8" BSP Male to connect to your own fitting.

*Other top fittings readily supplied to specification*

## Other Items



**Teflon tubing:**  
FEP 1/4" OD, 15m  
or 60m rolls.



**Mini Nondo Well Cover:**  
Small cover ideal for soil vapour installations. Only 150mm OD, 124mm ID, 150mm cast iron skirt, Flush mount, bolt down lid, oring sealed.

See Page 2 for Soil Vapour Implant options



FieldTech Solutions, makers of sustainable products.  
See [fieldtechsoln.com](http://fieldtechsoln.com) for more products  
designed to save our future resources

# Soil Vapour Implants and Weights



SVIFTS-6: Stainless steel mesh implant. 150mm long screen with barb connector at top. SVIFTSWSS Weight stainless steel (screw on) shown below.

SVIFTSWSS: Stainless steel weight, 22mm



SVPT97-6: Stainless steel mesh implant, reverse thread, 150mm long screen with barb connector at top. SVPT97B brass weight (screw on) shown below for use with Geoprobe® rods.

SVPT97B: Brass weight, reverse thread, 20mm.

## Do I need a weight?

Due to the coiled teflon tube acting like a spring, it can catch on the sides of the bore. For shallow installations of a few metres, a weight may not be necessary. For deeper installations, a weight is required to pull the implant down to the bottom.

## Ordering Information:

EC873301	Red push on cap
SVK1B	Sealing cap with push on fitting, dust cap included
R2003-0402	1/8" male thread push on fitting
SLB400C	Swagelok fitting for direct connection to Summa Cannister
TT33-15	Teflon tubing, 1/4" OD, 15m long, clear (or TT33.7-60 for 60m roll)
Nondo Mini	Mini Nondo well cover, cast iron, bolt down lid, flush mount, 150mm OD
SVIFTS-6	Soil vapour implant, 150mm screened mesh, stainless steel, with 1/4" barb (or SVPT95-6: reverse threaded for Geoprobe® tooling)
SVIFTSWSS	Stainless Steel weight for SVIFTS-6 soil vapour implant, 22mm
SVPT97B	Brass weight for SVPT95-6 Geoprobe style implant, 22mm, reverse thread



**FieldTech Solutions**

Tel - +61 3 9676 9664

37 Wirraway Drive, Port Melbourne, VIC.3207

Email - sales@fieldtechsoln.com